



AB048

- Maintainer Signature Select Series -

- Compartments are fully welded / adjustable shelving package / doors with gas spring holders, stainless steel hinges and three point D-Ring door latches
- 49" wide center deck floor with front bulkhead, rear swing-down tailgate and step bumper
- Body primed and undercoated
- I.C.C. round recessed LED lights, reflectors, mud flaps and rear body grab handles

- Galvaneal Steel Body and Options -

- 1 12' Long Dual Rear Wheel Galvaneal Steel Propane Body / Installed on chassis
145" long x 52" high x 16" deep compartments / 12-Gauge galvaneal compartment shell, 3/16" thk. 5052-H32 aluminum doors (reinforced), 1/8" steel center deck plate & 16" deep (bolt-on), full body width, step bumper w/ 2" square frame hitch receiver rated at Class IV (1,500 lb vert & 10,000 lb MGTW) and 7-prong flat blade (RV style) trailer plug
- 1 Adder to body for "Tall Tower Crane" 32,000 ft-lb max / includes body reinforcement w/ crane mount plate,
(2) crank outriggers - crane side manual out
- 1 Cab guard protector (headache rack) on front of service body
- 1 Large grab handle on CS crane and additional handle on rear OR tube for 3-pont contact
- 1 Step bumper deeper and 2nd step
- 1 Body setup for crane mounted on SS vs CS (only available in ST)
- 1 Adjustable boom saddle support
- 1 Add (2) springs to crane side of chassis for up to 6,500 lb cap. crane
- 1 3216 TT (tall tower - hydraulic) Crane 6,000 lbs max. capacity,
32,000 ft./lb., power extend 10'-16', power rotate, 25' remote cable
Note: Hydraulic cranes require a hydraulic power package below, crane valves are mounted on back of crane pedestals
- 1 4 foot manual extend from 16 - 20 feet on 3216 crane
- 1 Radio-wireless crane remote control, includes: engine start-stop, engine speed control, proportional control and ship along 33' cable for backup
- 1 Two rear hydraulic up / down in lieu of manual crank up / down outriggers
Note: This option is only for the hydraulic cranes
- 1 Holder on SS 1 rear door for (2) copper gas line rolls
- 1 Holder on SS 1 rear/back compartment wall for (1) PVC gas line roll
- 2 Swivel "J" hook on SS 1 front door
- 1 Roll-out tray with insert to carry (10) 4"x8"x16" blocks
- 1 Compartment to carry 4"x8"x16" blocks
- 1 Bolt Bin (LD) 18 drawers w/ drop-in dividers, 34"W x 13"H x 18"D
- 1 Hinge down vise mount on SS in front of crane
- 1 E-track on front cab guard & on top inside of SS compartment
- 1 Stake pocket rail on CS and on bottom inside of SS compartment

- Options for Aluminum and Steel Bodies-

- 1 Electric back up alarm - 97 db at 1 meter
- 1 Add charge to std PTO package for electric required on chassis w/ auto trans.
Ford F450-550 & Dodge 4500-5500
- 1 Electronic engine spd. control - computer set - electronic engine

- 1 Fire extinguisher - 20 lbs (ABC)
- 1 Mini ICC safety kit - 2 1/2 lb fire ext. ABC, hazard reflectors
- 1 Four hazard placard flip triangles - required w/110 gal. or greater
- 1 Open center hydraulic power package, includes PTO, pump, std oil reservoir w/ in-tank filter, vent fill cap, sight gauge
- 2 Exterior 12 v. flood light (halogen)
- 1 Flood lights to come on with chassis back up
- 2 Interior 12 v. LED strip light (can be used in O/A compartments)
- 12 Feet of unit painted urethane "White" color / List Code:
 - Not a base coat/clear coat or Metallic
 - Note: Due to variations in OEM paint products and application methods, Maintainer cannot guarantee a perfect paint match on color
- 12 Feet of Protective Spray Covering - cargo center deck, compartment top & side, bumper
- 1 Front cab guard, stake pockets rails, block inserts and wheel chock holder
- 12 Feet of PPG-splatter-paint interior compartment finish on painted bodies
- 1 5" Wilton vise - model 675 w/ 5.5" opening
- 1 Tire chocks (two)
- 1 Storage bracket for tire chock storage SS rear under crane valve compartment
- 1 4-Pocket removeable shovel storage rack