

AC201 Maintainer MTS 3216TT-1-084 Service Body

- Maintainer Service Body (MTS) Features -
- Galvanneal body to resist corrosion including body shell (14 / 12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Cabinet floor reinforcement w/ clean-out drains
- Three point D-ring door latches w/ gas spring door holders
- Adjustable shelving package
- 49" Wide center deck overlaid with deck plating
- 10" Swing-down tailgate
- 12" Deep, full body width, step bumper w/ 2" square frame hitch receiver rated at Class IV (1,500 lb vert & 10,000 lb MGTW) and 7-prong flat blade (RV style) trailer plug
- Fuel fill(s) recessed into body side rail (1-ton only)
- Body primed, undercoated and includes back-up alarm
- I.C.C. round recessed LED lights, reflectors, mud flaps and rear body grab handles
- Mini I.C.C. Safety kit 2 1/2 pound ABC fire extinguisher & hazard reflectors
 - 1 MTS-1-084, 52" High X 23" Deep Compartments, 11' Long Body, 14 / 12 Ga. body, 44" x 21" wheel well opening / installed on chassis
 - 1 Adder for 1 or 2 ton service body "Tall Tower Crane" reinforcement structure of body

NOTE: For individual crane equipment & accessory items ie. adj. boom saddle, outrigger pkgs., body leveling pkgs., hyd. pkgs. to operate a crane or other hyd. drive components - Contact Factory

- 1 Add 1/2' (half foot) to rear compartment for extended rear chassis fuel tank
- 5 Feet of 59" tall compartments in lieu of 52" (PS-1 & PS-2)
 - Hydraulic Cranes (Tall or Short Tower) -

All cranes include a closed center load sensing hydraulic power package consist of a PTO, CC/LS pump, oil reservoir w/ in-tank filter-vented fill cap - sight gauge - suction screen & ball valve, 33 foot remote control w/ proportional trigger & engine start/stop, hydraulic fully extend boom, anti-two block system, overload protection, holding valves, adjustable boom saddle and body spring leveling package (note if air suspension customer will be required to have chassis OEM to provide dual-control)

- 1 3216 Crane 6,000 lb. max. capacity w/ hydraulic extend boom 10' to 16' w/ 2 rear hydraulic up/down & 1 manual out crane side outriggers
 - Crane Equipment & Accessories -
- 1 Two rear manual crank up / down outriggers in lieu of hydraulic up / down

- Chassis Equipment & Accessories -
- Add charge to std PTO package for electric required on chassis w/ auto trans. Ford F450-550 & Dodge 4500-5500
- 1 Electronic engine spd. control computer set electronic engine
 - Hydraulic Equipment & Accessories -
- 1 Open center hydraulic pump system in lieu of closed center load sensing
 - Compressor Equipment & Accessories -
- 1 Quincy 24.8 CFM @ 100 PSI hydraulic driven recip. air compressor w/ cover w/ 20 gallon air tank / 22.1 CFM @ 150 PSI, 37 CFM displac. hydraulic oil cooler built into assembly
- 1 Air accessory package filter / lubricator / regulator 3/8" X 30' spring rewind reel, hose & ball stop
- 1 Hose reel access out rear compartment
- 1 Cargo area side of air compressor to have slotted cover w/ Durabed (008513)
 - Compartment Equipment & Accessories -
- Oxy/Act bottle storage w/ratchet strap, vents, "J" hks. & re/flr. (PS-2)
 - Lighting / Electrical Equipment & Accessories -
- 1 Exterior 12 v. lighting pkg. (halogen) 1-permanent & 1-remote
 - Painting Equipment & Accessories -
- 11.5 Feet of unit painted urethane "White" color / List Code:

Not a base coat/clear coat or Metallic

Note: Due to variations in OEM paint products and application methods,

Maintainer cannot guarantee a perfect paint match on color

- 11.5 Feet of PPG-splatter-paint interior compartment finish on painted bodies
 - Center Deck Equipment & Accessories -
- 4 Flush mount "D" ring tie-downs in bed floor, each
 - Rear Bumper Equipment & Accessories -
- 1 Rear bumper, and panel located 3" back of normal position, lights flush mounted (no boxes)
- 1 Custom bumper height for standard step bumper shorter than standard
- 1 Step bumper to have recess for 2" receiver
- 1 Step bumper to have recessed pocket to allow for crane valve "T" handles