

Stock#: D648

QTY	DESCRIPTION	NOTE
	Dutec Service Body with Crane	
1	Body Subframe: 6" x 3/16" Crossmembers, 10 Ga Longitudinal Floor Reinforcement	
	Low Floor Height (Only 6" Above Chassis Frame)	
	Floor: 1/8" Treadplate	
	Compartment Tops & Rears: 1/8" Treadplate	
1	Crane Compartment: 3/8" H.R. Steel w/ 1/2" H.R. Top Plate & 4x3x1/2" Angle Reinforcement. Completely Open for Storage.	
	Major Body Components: 12 Ga & 10 Ga H.R.P.O.	
	Body Designed w/ Appropriate Material Eliminating Overlays w/ Rust Pockets	
	Superior Weather Tight Double Panel Galvannealed Doors, Automatic Type Replaceable Bulb Rubber Seals	
	Over Center Spring Loaded Door Restraints	
	Spring Mounting Kit	
	Greasable XHD Hinges w/ 5/16" Stainless Steel Pins	
	Stainless Steel D-Ring Latches	
	22" Deep Compartments	
	12 Ga Formed Tailgate / Work Table	
	Die Formed Ribs in Front Bulkhead	
	Recessed Cargo Tie Down Rings	
	All Exterior Welds Are Continuos Fully Penetrating Welds	
	*No Caulking is Used on These Bodies	
	HD Shelf Support Strips	
	Anti Rattle Shelf Dividers	
	A Factory Installed Wiring Loom is Provided w/ Each Crane Body	
	*Stop, Turn, Tail Lights are Sealed Beams	
	Additional Equipment & Accessories	
1	P2 - 60" Tall Raised & Vented Oxy/Act Bottle Compartment w/ Reinforced Floor / Bottle Retension System,	
	Hose Bracket, Torch Gauge Brackets & Hose Wrap Mounted on Door of P2	
1	D1, D2 & P1 - 60" Tall Raised Compartment	
2	Adjustable Shelves w/ Dividers in Each Vertical Compartment	
1	Adjustable Divider Shelf w/ Dividers in Each Horizontal Compartment	
1	Boom Rest	
1	Compression Door Latches	
2	Manual Out & Down Side Crane Outriggers	
1	15" Long x 5' Tall HD Step Bumper	
1	Class IV Receiver Hitch rated at 10,000lb Gross Towing Weight & 1,000-1,200lb's Tongue Weight	
1	7-Way Flat Blade Trailer Plug	