Subject: D152 / Dutec DSD 84 CB Service Body

- Standard Features -

* Body Subframe: 6" x 3/16" Crossmembers,
  10 Ga Longitudinal Floor Reinforcement
* Low Floor Height (Only 6" Above Chassis Frame)
* Floor: 1/8" Treadplate
* Compartment Tops & Rears: 1/8" Treadplate
* Crane Compartment: 3/8" H.R. Steel w/ 1/2" H.R. Top Plate &
  4x3x1/2" Angle Reinforcement. Completely Open for Storage.
* Major Body Components: 12 Ga & 10 Ga H.R.P.O.
* Body Designed w/ Appropriate Material Eliminating
  Overlays w/ Rust Pockets
* Superior Weather Tight Double Panel Galvannealed Doors
  Automatic Type Replaceable Bulb Rubber Seals
* Over Center Spring Loaded Door Restraints
* Spring Mounting Kit
* Greasable XHD Hinges w/ 5/16" Stainless Steel Pins
* Stainless Steel D-Ring Latches
* 22" Deep Compartments
* 12 Ga Formed Tailgate / Work Table
* Die Formed Ribs in Front Bulkhead
* Recessed Cargo Tie Down Rings
* All Exterior Welds Are Continuos Fully Penetrating Welds
  No Caulking is Used on These Bodies
* HD Shelf Support Strips
* Anti Rattle Shelf Dividers
* A Factory Installed Wiring Loom is Provided w/ Each Crane Body
  Stop, Turn, Tail Lights are Sealed Beams

- Additional Equipment & Accessories -

1   P2 - 60" Tall Raised & Vented Oxy/Act Bottle Compartment
w/ Reinforced Floor / Bottle Retension System, Hose Bracket, Torch
Gauge Brackets & Hose Wrap Mounted on Door of P2

1   D1 & P1 - 60" Tall Raised Compartment

2   Adjustable Shelves w/ Dividers in Each Vertical Compartment

1   Adjustable Divider Shelf w/ Dividers in Each Horizontal Compartment

1   Boom Rest

1   Compression Door Latches

2   Manual Out & Down Side Crane Outriggers

1   15" Long x 6" Tall HD Step Bumper w/ Toe Steps

1   Class IV Receiver Hitch rated at 10,000lb Gross Towing Weight &
1,000-1,200lb's Tongue Weight

1   7-Way Flat Blade Trailer Plug

1   Liftmoore Crane Model 6036WX-20 w/ 6,000lb. Max Capacity
Electric / Hydraulic w/ Power Boom Extension 10' - 16'
4' Manual Extension w/ 20' Total Reach