



Subject: D312 / Dutec DSD 84 CB Service Body

- Standard Features -

- * Body Subframe: 6" x 3/16" Crossmembers,
10 Ga Longitudinal Floor Reinforcement
- * Low Floor Height (Only 6" Above Chassis Frame)
- * Floor: 1/8" Treadplate
- * Compartment Tops & Rears: 1/8" Treadplate
- * Crane Compartment: 3/8" H.R. Steel w/ 1/2" H.R. Top Plate &
4x3x1/2" Angle Reinforcement. Completely Open for Storage.
- * Major Body Components: 12 Ga & 10 Ga H.R.P.O.
- * Body Designed w/ Appropriate Material Eliminating
Overlays w/ Rust Pockets
- * Superior Weather Tight Double Panel Galvannealed Doors
Automatic Type Replaceable Bulb Rubber Seals
- * Over Center Spring Loaded Door Restraints
- * Spring Mounting Kit
- * Greasable XHD Hinges w/ 5/16" Stainless Steel Pins
- * Stainless Steel D-Ring Latches
- * 22" Deep Compartments
- * 12 Ga Formed Tailgate / Work Table
- * Die Formed Ribs in Front Bulkhead
- * Recessed Cargo Tie Down Rings
- * All Exterior Welds Are Continuous Fully Penetrating Welds
No Caulking is Used on These Bodies
- * HD Shelf Support Strips
- * Anti Rattle Shelf Dividers
- * A Factory Installed Wiring Loom is Provided w/ Each Crane Body
Stop, Turn, Tail Lights are Sealed Beams

- Additional Equipment & Accessories -

- 1 P2 - 60" Tall Raised & Vented Oxy/Act Bottle Compartment
w/ Reinforced Floor / Bottle Retention System, Hose Bracket, Torch
Gauge Brackets & Hose Wrap Mounted on Door of P2
- 1 D1, D2 & P1 - 60" Tall Raised Compartment
- 2 Adjustable Shelves w/ Dividers in Each Vertical Compartment
- 1 Adjustable Divider Shelf w/ Dividers in Each Horizontal Compartment
- 1 Boom Rest
- 1 Compression Door Latches
- 2 Manual Out & Down Side Crane Outriggers
- 1 15" Long x 5" Tall HD Step Bumper
- Bar Storage Compartment & Removable Vise Plate
- 1 Class IV Receiver Hitch rated at 10,000lb Gross Towing Weight &
1,000-1,200lb's Tongue Weight
- 1 7-Way Flat Blade Trailer Plug

- 1 Liftmoore Crane Model 6036WX-20 w/ 6,000lb. Max Capacity
Electric / Hydraulic w/ Power Boom Extension 10' - 16'
4' Manual Extension w/ 20' Total Reach