


Equipment Technology, LLC

SITE MAP
CONTACT US

COMPANY
EQUIPMENT
PARTS & ACCESSORIES
CUSTOMER SERVICES

GO

## AERIAL LIFTS

Articulating  
 Articulating - Over Center  
 Articulating - Material Handler  
 Telescopic  
 Articulating - Telescopic Combination

## FINANCE

Leasing Options

## EQUIPMENT | INSULATED AERIAL LIFTS

### ■ ARTICULATING - TELESCOPIC COMBINATION

- Continuous rotation is standard on all insulated ETC units.
- Full pressure hydraulic controls located at basket and turret w/ full feathering capacities from both upper and lower controls.
- Hydraulic leveling via master/slave system providing a bucket dump for clean out and operator rescue.
- Shear ball rotation gear driven by external drive gear box. The gear box has an extended shaft for manual rotation.
- Internally mounted holding valves (integral part of cylinder) lock cylinders in place in the event of hydraulic failure.
- All pins turn on replaceable bushings.
- Hydraulic cylinder extension of inner boom providing maximum clear span of inner boom for insulation.



### ■ GENERAL SPECIFICATIONS

	ETC 37 IH (Insulated)
<b>Height to Bottom of Bucket*</b>	37'
<b>Working Height*</b>	42'
<b>Stowed Height*</b>	10'
<b>Rotation</b>	Continuous

\* Based on 36" frame height

***ETI manufactured equipment meets or exceeds OSHA, ANSI 92.2 and FMVSS standards at time of manufacture.***

[Top](#)

**Call us at 1-888-748-3841 or 405-748-3841**

©2009 Equipment Technology®, LLC All rights reserved. [Legal Info](#)