



V203 / 6729

- Galvanized body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Cabinet floor reinforcement w/ clean-out drains
- Three point composite D-ring door latches w/ gas shock door holders
- Adjustable shelving package
- 49" Wide center deck overlaid with deck plating
- 10" Swing-down tailgate
- 12" Deep, full body width, step bumper w/ 2" square frame hitch receiver Class IV
- Fuel fill recessed into body side rail (1-ton only)
- Body primed and undercoated
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles
- Mini I.C.C. Safety kit - 2 1/2 pound ABC fire extinguisher & hazard reflectors

1 MTS-1-084-LP, 42" High X 23" Deep Compartments, 11' Long Body,
12 Ga. body, 44" x 21" wheel well opening / installed on chassis
1 Adder for 1 or 2 ton service body "Short Tower Crane"
reinforcement structure of body & crane compartment

NOTE: For individual crane equipment & accessory items ie. adj.
boom saddle, outrigger pkgs., body leveling pkgs., hyd. pkgs. to
operate a crane or other hyd. drive components - Contact Factory

1 Ref. UPRR spec 41

- Hydraulic Cranes (Tall or Short Tower) -

All cranes include a closed center load sensing hydraulic power package consist
of a PTO, pump, oil reservoir w/ in-tank filter-vented fill cap - sight gauge - suction
screen & gate valve, 25 foot remote control, hydraulic extend boom, anti-two block
system, hydraulic overload protection, holding valves and proportional trigger
control, adjustable boom saddle and body spring leveling package (note if air
suspension customer will be required to have chassis OEM to provide dual-control)

1 1115 Crane 3,500 lb. max. capacity w/ hydraulic extend boom 7' to 11' and
manual 11' to 15'
w/ 2 - rear hydraulic up/down & 1 - manual out crane side outriggers

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Cabinet floor reinforcement w/ clean-out drains
- Three point composite D-ring door latches w/ gas shock door holders
- Adjustable shelving package
- 49" Wide center deck overlaid with deck plating
- 10" Swing-down tailgate
- 12" Deep, full body width, step bumper w/ 2" square frame hitch receiver Class IV
- Fuel fill recessed into body side rail (1-ton only)
- Body primed and undercoated
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles
- Mini I.C.C. Safety kit - 2 1/2 pound ABC fire extinguisher & hazard reflectors

1 MTS-1-084-LP, 42" High X 23" Deep Compartments, 11' Long Body,
12 Ga. body, 44" x 21" wheel well opening / installed on chassis

1 Adder for 1 or 2 ton service body "Short Tower Crane"
reinforcement structure of body & crane compartment

NOTE: For individual crane equipment & accessory items ie. adj. boom saddle, outrigger pkgs., body leveling pkgs., hyd. pkgs. to operate a crane or other hyd. drive components - Contact Factory

1 Ref. UPRR spec 41

- Hydraulic Cranes (Tall or Short Tower) -

All cranes include a closed center load sensing hydraulic power package consist of a PTO, pump, oil reservoir w/ in-tank filter-vented fill cap - sight gauge - suction screen & gate valve, 25 foot remote control, hydraulic extend boom, anti-two block system, hydraulic overload protection, holding valves and proportional trigger control, adjustable boom saddle and body spring leveling package (note if air suspension customer will be required to have chassis OEM to provide dual-control)

1 1115 Crane 3,500 lb. max. capacity w/ hydraulic extend boom 7' to 11' and manual 11' to 15'
w/ 2 - rear hydraulic up/down & 1 - manual out crane side outriggers

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Cabinet floor reinforcement w/ clean-out drains
- Three point composite D-ring door latches w/ gas shock door holders
- Adjustable shelving package
- 49" Wide center deck overlaid with deck plating
- 10" Swing-down tailgate
- 12" Deep, full body width, step bumper w/ 2" square frame hitch receiver Class IV
- Fuel fill recessed into body side rail (1-ton only)
- Body primed and undercoated
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles
- Mini I.C.C. Safety kit - 2 1/2 pound ABC fire extinguisher & hazard reflectors

1 MTS-1-084-LP, 42" High X 23" Deep Compartments, 11' Long Body,
 12 Ga. body, 44" x 21" wheel well opening / installed on chassis
 1 Adder for 1 or 2 ton service body "Short Tower Crane"
 reinforcement structure of body & crane compartment

NOTE: For individual crane equipment & accessory items ie. adj. boom saddle, outrigger pkgs., body leveling pkgs., hyd. pkgs. to operate a crane or other hyd. drive components - Contact Factory

1 Ref. UPRR spec 41

- Hydraulic Cranes (Tall or Short Tower) -

All cranes include a closed center load sensing hydraulic power package consist of a PTO, pump, oil reservoir w/ in-tank filter-vented fill cap - sight gauge - suction screen & gate valve, 25 foot remote control, hydraulic extend boom, anti-two block system, hydraulic overload protection, holding valves and proportional trigger control, adjustable boom saddle and body spring leveling package (note if air suspension customer will be required to have chassis OEM to provide dual-control)

1 1115 Crane 3,500 lb. max. capacity w/ hydraulic extend boom 7' to 11' and manual 11' to 15'
 w/ 2 - rear hydraulic up/down & 1 - manual out crane side outriggers