



Subject: V352 - 6721 / Maintainer Lube Body

- Standard Features -

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Doors are single piece construction to avoid water traps
- Three point D-Ring door latches / Gas Shock door holders
- Under body is undercoated to resist corrosion w/ reinforcements and drain plugs
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles

13.5 Feet of heavy duty lube bed w/ I.C.C. bumper: Multi-leaf or air suspension recommended / other suspension types consult factory for approval

- 1 Galvannealed rear reel compartment w/ aluminum roll-up access door, rear vapor proof switch panel & open grated deck span in rear step
- 4 Galvannealed underbody storage compartment
- 2 Galvannealed abovebody storage compartment
- 1 Permanent steps built recessed into side of bed
- 1 Install charge to mount lube body on chassis
- 1 All compartment latches are to be stainless steel.

- Chassis Equipment & Accessories -

- 1 Relocate chassis battery
- 1 Electric back up alarm - 97 db at 1 meter
- 1 PTO Allison (MD, HD, 1000, 2000 & 2400) auto transmission
- 1 Electronic engine spd. control - computer set - electronic engine
- 1 Mini ICC safety kit - 2 1/2 lb fire ext. ABC, hazard reflectors
- 1 Fire extinguisher - 20 lbs (ABC)
- 1 Four hazard placard flip triangles - required w/110 gal. or greater

- Hydraulic Equipment & Accessories -

- 1 Closed center LS hydraulic power package, includes PTO, pump, oil reservoir 20-30 gallon w/ in-tank filter, vent fill cap, sight gauge
- 1 Larger oil reservoir (40-60 gallon) in lieu of 20-30
- 1 PTO driveline or adaptor - std. displacement hydraulic pump
- 1 HP 5 Micron Filter recommended for Hydraulic oil
- 1 HP 25 Micron Filter recommended for engine oil

- Compressor Equipment & Accessories -

- 1 Model 37 displac. CFM hydraulic driven recip. air compressor w/ cover w/ 20 gallon air tank / 24.8 CFM @ 100 PSI / 22.1 CFM @ 150 PSI hydraulic oil cooler build into assembly
- 1 Air accessory package - filter / lubricator / regulator 1/2" X 50' spring rewind reel, hose & ball stop
- 4 Adjustable shelves

- Lighting Equipment & Accessories -

- 7 Exterior 12 v. flood light (halogen)

- Painting Equipment & Accessories -

- 2 Paint body complete - one solid urethane color

Note: Due to variations in OEM paint products and application methods, Maintainer cannot guarantee a perfect paint match on colors or metallics.
Note: For metallics or clear coat/base coat paint additional charges will be required and are not included in this quote unless shown

- 1 Line-X protective spray covering - deck platform and reel compartment interior

- Roll-out Drawer and Tray Equipment & Accessories -

- 1 Used filter storage cabinet mounted on roll-out tray
- 1 Used filter storage cabinet plumbed into evac system

- Rear Bumper Equipment & Accessories -

- 1 Rear Bumper to be full treadplate.

- Miscellaneous Equipment & Accessories -

- 1 Vise / grinder removable mounting plate

- Lube Tanks -

Tanks equipped with lockable vented fill caps, suction screen, guarded sight gauge, shut-off valve on tank suction line and tank baffles.

- Steel Lube Tanks -

- 4 51-100 gallon steel tank: (4) 100 gal.
- 4 101-200 gallon steel tank:(2) 150 gal. & (2) 175 gal.
- 1 201-300 gallon steel tank: (1) 300 gal EVAC

- Stainless Steel Lube Tanks -

- 1 0-50 gallon stainless steel tank:(1) 40 gal. A/F

- Tank Racks -

- 2 201-500 gallon tank rack: (1) 400 gal & (1) 300 gal tank rack
- 1 501-1000 gallon tank rack:(1) 600 gal tank rack

- Hydraulic Driven Pump Kits -

- 8 Hydra Kit #1 Oil - Commercial-Shearing pump (small displacement)
0-8 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.
0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.
Hannay 1/2" X 50' spring reel & high-flow non-drip dispenser
- 1 Hydra Kit #4 Water / Anti-Freeze - Hypro pump
0-10 GPM delivery
Hannay 1/2" X 50' spring rewind
high-flow non-drip dispenser
- 1 Hydra Kit #5 Evacuation - Commercial-Shearing pump
0-10 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.
0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.
Hannay 1" X 30' spring reel, 4-way control & suction screen

- Air Driven Pump Kits -

- 1 Air Kit #12 120# Grease Kit - Graco 50:1 pump (regulator & oiler)
drum cover, follow plate & tie down
Hannay 3/8" X 50' spring rewind reel w/ high pressure swivel
dispenser with swivel

- Lube Equipment & Accessories -

- 8 Dial oil meter 4 GPM w/ non-drip dispenser in lieu of std.