BZ SERIES CANTILEVER LEVEL LIFT

In 3300 lb. and 4400 lb. Now with **Capacities** U.S. Made **Power Unit And Controls** SERIES

LARGE PLATFORM AND WIDE-ARM CONFIGURATION IMPROVE DELIVERY EFFICIENCY

The Waltco BZ Series Level Lift cantileverstyle liftgates combine the large, full-width platform capability of the conventionalstyle liftgate with the load-leveling convenience of the cantilever gate. The BZ Series' tilting feature lets the operator maintain a level platform on most any terrain – with push-button simplicity. The special wide-arm configuration accommodates stationary receiver-type trailer hitches for multi-purpose applications.

Increase Your Productivity

Maximize the delivery potential of your vehicle. Large, level-ride platform accommodates bulky, wide or heavy cargo. Wide-arm configuration makes the BZ Series Level Lift compatible with vehicles also equipped with stationary receivertype hitches.

Make Your Life Easier

Hydraulically powered platform lets operators open and close the platform with a simple push-button control. The BZ Series Level Lift is faster and easier to operate because operators never have to manually fold the platform.

Reduce Your Risk

The thermally protected power unit minimizes costly downtime by alerting the operator before heat build-up can cause permanent damage to the electrical components. Electronic cylinder locks prevent the platform and cargo from lowering in the event of a hydraulic line failure. The platform stores hydraulically against the rear of the vehicle to discourage unauthorized entry into the cargo area of the truck.

Improve Your Profitability

The BZ Series Level Lift cantilever-style liftgate accommodates both roll-up and swing doors. Swing doors let you maximize cargo space. More cargo per load translates into greater profitability.

WALTCOHYDRAULIC LIFTGATES

BZ Series Cantilever Level Lift



SPECIFICATIONS

MODEL	LIFTING	PLATFORM	BED HEIGHT	APPROX.
	CAPACITY*	LOAD AREA	RANGE**	WEIGHT
BZ-33	3300 lbs.	48" x 94"	36"-59"	1105 lbs.
BZ-33	3300 lbs.	60" x 94"	36"-59"	1200 lbs.
BZ-33	3300 lbs.	72" x 94"	36"-59"	1295 lbs.
BZ-33	3300 lbs.	84" x 94"	36"-59"	1330 lbs.
BZ-44	4400 lbs.	48" x 94"	36"-59"	1155 lbs.
BZ-44	4400 lbs.	60" x 94"	36"-59"	1250 lbs.
BZ-44	4400 lbs.	72" x 94"	36"-59"	1345 lbs.
BZ-44	4400 lbs.	84" x 94"	36"-59"	1380 lbs.

*Platform may be loaded to full-rated capacity if cargo load center is no further than 24" from the rear of the vehicle.

Standard Features Ensure Reliable Performance, Ease Of Use, And Enhanced Productivity

- Large, cantilever platform keeps cargo level on all types of terrain and allows the operator to load and unload cargo from either the rear or the side of the platform.
- Hydraulically powered open/close feature makes liftgate operation faster and easier by eliminating the need for manual folding.
- Adjustable tilt cylinders prevent potential damage to the liftgate or vehicle by preventing over-tilting of the platform.
- Electronic cylinder locks prevent the platform and cargo from lowering in the event of a hydraulic line failure.
- Thermally protected power unit safeguards liftgate motor from damage due to heat build-up.

- Dual-lift and dual-tilt cylinder design allows for more positive platform control, greater load stability, and enhanced speed and reliability even in cold temperatures.
- Hand-held remote control lets the driver raise and lower the liftgate from ground or bed level.
- Weather-resistant power unit enclosure protects liftgate power unit from corrosion and environmental damage.
- Platform marker lights provide increased visibility and safety while the liftgate platform is in the open working position.
- Power shut-off switch prevents unauthorized use of the liftgate.
- Steel bumper protects liftgate chassis from backing damage.
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion.

OPTIONAL EQUIPMENT

- Full-Door Seal Kit
- Power Kits for straight truck and trailers.
- Threshold Spacer Kit (recommended for swing door applications) spaces the liftgate platform away from the rear threshold of the vehicle providing clearance for door locking hardware.
- Split Foot Activated Cart Stops keep rolling carts secure on the platform while the platform is being lowered, raised or leveled. The independent stops allow the operator to move a single cart off the platform, while the second remains retained.
- Auto-tilt Option with Memory tilts the platform down at ground level for ease loading/unloading and returns the platform to a preset horizontal position.
- 98" Wide Steel Platforms for 102" wide vehicle applications.
- Aluminum Plaforms: 65", 75", and 85" depths (contact factory.)
- Customized Options for specific applications. WALTCO's Custom Solutions team can modify the BZ Series to meet your specific delivery requirements.





CONTACT THE LIFTGATE PROFESSIONALS...

PHONE: (800) 211-3074 FAX: (800) 211-3075

WWW.WALTCO.COM

CORPORATE OFFICES 285 Northeast Ave. Tallmadge, OH 44278

CALIFORNIA Gardena, CA GEORGIA Marietta, GA TEXAS Dallas, TX









^{**}See installation manual or contact factory for exact mounting dimensions.