



Z047 Equipment

- Standard Features -

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Doors are single piece construction to avoid water traps
- Three point D-Ring door latches / Gas Shock door holders
- Under body is undercoated to resist corrosion w/ reinforcements and drain plugs
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles

- 11 Feet of medium duty lube bed w/ I.C.C. bumper: Multi-leaf or air suspension recommended / other suspension types consult factory for approval
- 1 Reel rack without cover
- 1 Fold-up deck access ladder on top of bed
- 1 Assembly charge for ship-out lube body
- 1 Rear step bumper
- 1 Air Manifold for single air supply hook up

- Chassis Equipment & Accessories -

- 1 Four hazard placard flip triangles - required w/110 gal. or greater

- Painting Equipment & Accessories -

- 1 Paint body complete - one solid urethane color / List color:
Note: Due to variations in OEM paint products and application methods, Maintainer cannot guarantee a perfect paint match on colors or metallic.
Note: For metallic or clear coat/base coat paint additional charges will be required and are not included in this quote unless shown

- Lube Tanks -

Tanks equipped with filtered fill caps, suction screen, guarded sight gauge, shut-off valve on tank suction line, tank baffles and tank rack

- Steel Lube Tanks -

- 4 50 gallon steel tanks - (3) oils & (1) evac
- 1 500 gallon steel tank - diesel

- Air Driven Pump Kits -

- 3 Air Kit #1 Oil - Graco pump (regulator & oiler)
5:1 ratio, 0-3 GPM delivery (consult factory for oil type)
Hannay 1/2" X 50' spring rewind reel
high-flow non-drip rigid dispenser
- 1 Air Kit #8 Evacuation - diaphragm pump (regulator)
0-15 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.
0-8 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.
Hannay 1" X 30' spring rewind reel, 4-way control & suction screen

- Lube Equipment & Accessories -

- 1 Cable operated emergency fuel shut-off w/ fusible link
- 1 Fill-Rite 12 volt fuel pump w/ 25' hose and nozzle