



Z126 Equipment

- Standard Features -

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Doors are single piece construction to avoid water traps
- Three point D-Ring door latches / Gas Shock door holders
- Under body is undercoated to resist corrosion w/ reinforcements and drain plugs
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles

- 11 Feet of heavy duty lube bed w/ I.C.C. bumper: Multi-leaf or air suspension recommended / other suspension types consult factory for approval
- 1 Galvannealed rear reel compartment w/ aluminum roll-up access door, rear vapor proof switch panel & open grated deck span in rear step
- 2 Galvannealed above body storage compartment
- 2 Permanent steps built recessed into side of bed
- 1 Fold-up deck access ladder on top of bed
- 1 Install charge to mount lube body on chassis

- Chassis Equipment & Accessories -

- 1 Relocate chassis battery
- 1 Electric back up alarm - 97 db at 1 meter
- 1 Power-assist shift PTO (for "Hot Shift PTO" consult factory)
- 1 Electronic engine spd. control - computer set - electronic engine
- 1 Mini ICC safety kit - 2 1/2 lb fire ext. ABC, hazard reflectors
- 1 Fire extinguisher - 20 lbs (ABC)
- 1 Four hazard placard flip triangles - required w/110 gal. or greater

- Hydraulic Equipment & Accessories -

- 1 Closed center LS hydraulic power package, includes PTO, pump, std oil reservoir w/ in-tank filter, vent fill cap, sight gauge
- 1 Large oil reservoir in lieu of std
- 1 PTO driveline or adaptor - std. displacement hydraulic pump

- Compressor Equipment & Accessories -

- 1 Model 37 displac. CFM hydraulic driven recip. air compressor w/ cover w/ 20 gallon air tank / 24.8 CFM @ 100 PSI / 22.1 CFM @ 150 PSI hydraulic oil cooler build into assembly
- 1 Air accessory package - filter / lubricator / regulator 1/2" X 50' spring rewind reel, hose & ball stop

- Compartment Equipment & Accessories -

- 2 Adjustable shelf

- Lighting / Electrical Equipment & Accessories -

- 7 Exterior 12 v. flood light (halogen)
- 4 Interior 12 v. strip light
- 1 LED tail, back-up and marker lighting in lieu of std. #007313

- Painting Equipment & Accessories -

- 3 Paint body complete - one solid urethane color / List color:
Note: Due to variations in OEM paint products and application methods, Maintainer cannot guarantee a perfect paint match on colors or metallic.
Note: For metallic or clear coat/base coat paint additional charges

- will be required and are not included in this quote unless shown
- 1 Line-X protective spray covering - deck platform & steps, above body compartments and reel compartment top, front & interior
- Roll-out Drawer and Tray Equipment & Accessories -
- 1 Used filter storage cabinet mounted on roll-out tray
- 1 Used filter storage cabinet plumbed into evac system
- Lube Tanks -
- Tanks equipped with filtered fill caps, suction screen, guarded sight gauge, shut-off valve on tank suction line, tank baffles and tank rack
- Steel Lube Tanks -
- 5 Steel tanks; (2) 80 gal. 90WT, 30WT & (3) 100 gal: for 15/40, HYD, 50WT oils
- 1 300 gallon steel tank; EVAC
- Stainless Steel Lube Tanks -
- 1 100 gallon stainless steel tank; Anti-Freeze
- Plastic Lube Tanks and Other Tank Accessories -
- 1 "Tank Full" indicator light
- Oval Tank -
- 1 Oval tank comes equipped with sump, access ladder, manhole fill & undertank compartments.
1750 gallon oval tank
- Hydraulic Driven Pump Kits -
- 5 Hydra Kit #1 Oil - Commercial-Shearing pump (small displacement)
0-8 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.
0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.
Hannay 1/2" X 50' spring reel & high-flow non-drip rigid dispenser
- 1 Hydra Kit #4 Anti-Freeze - Hypro pump (non-corrosion resistant)
0-10 GPM delivery
Hannay 1/2" X 50' spring rewind (non-corrosion resistant)
high-flow non-drip rigid dispenser
- 1 Hydra Kit #6 Evacuation - Commercial-Shearing pump
0-15 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.
0-8 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.
Hannay 1 1/2" X 40' spring reel, 4-way control & suction screen
- 1 Hydra Kit #9 Fuel - Roper 3611 pump
40-50 GPM delivery
Hannay 1 1/4" X 50' spring rewind reel
1 1/2" OPW dispenser & swivel
- Air Driven Pump Kits -
- 1 Air Kit #13 400# Grease Kit - Graco 50:1 pump (regulator & oiler)
drum cover, follow plate & tie down
Hannay 3/8" X 50's spring rewind reel w/ high pressure swivel
dispenser with swivel
- Lube Equipment & Accessories -
- 1 Air operated emergency fuel shut-off w/ fusible link
- 1 Fuel meter 0-60 GPM
- 1 (ZNC2A) Diesel external mount receiver, with cap
- 1 (ZV10C) Diesel fuel vent