



Z181 - 6371CB

- Standard Features -

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Doors are single piece construction to avoid water traps
- Three point D-Ring door latches / Gas Shock door holders
- Under body is undercoated to resist corrosion w/ reinforcements and drain plugs
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles

- 20 Feet of heavy duty lube bed w/ I.C.C. bumper: Multi-leaf or air suspension recommended / other suspension types consult factory for approval
- 1 Galvannealed rear reel compartment w/ aluminum roll-up access door, rear vapor proof switch panel & open grated deck span in rear step
- 4 Galvannealed underbody storage compartment
- 3 Galvannealed above body storage compartment
- 1 Permanent steps built flush on outside of bed
- 1 Permanent steps built recessed into side of bed
- 1 Install charge to mount lube body on chassis

- Chassis Equipment & Accessories -

- 1 Electric back up alarm - 97 db at 1 meter
- 1 Electronic engine spd. control - computer set - electronic engine
- 1 Mini ICC safety kit - 2 1/2 lb fire ext. ABC, hazard reflectors
- 1 Fire extinguisher - 20 lbs (ABC)
- 1 Four hazard placard flip triangles - required w/110 gal. or greater

- Hydraulic Equipment & Accessories -

- 1 PTO driveline - high displacement hydraulic pump
- 1 Lrg. closed center LS hydraulic power pkg, includes PTO, lrg. pump, large oil reservoir w/ in-tank filter, vent fill cap, sight gauge
- 1 Hydraulic cooling package, high efficiency bar/plate design, low-med GPM flow rating - consult factory for usage application

- Compressor Equipment & Accessories -

- 1 Model 37 displac. CFM hydraulic driven recip. air compressor w/ cover w/ 20 gallon air tank / 24.8 CFM @ 100 PSI / 22.1 CFM @ 150 PSI hydraulic oil cooler build into assembly
- 1 Air accessory package - filter / lubricator / regulator 1/2" X 50' spring rewind reel, hose & ball stop

- Generator Equipment & Accessories -

- 1 Hydraulic generator - 4800 watt - 110 & 220 volt
- 1 Sealed duplex electrical outlet / C/S front / wire to generator, in conduit

- Compartment Equipment & Accessories -

- 6 Adjustable shelf
- 2 Bolt-in center deck storage boxes 22"W x 25"T x (1) 60"LG. & (1) 48"LG
- 1 Center deck boxes are to have hinge-up lids (more water tight) w/ gas shock assist

- Lighting / Electrical Equipment & Accessories -

- 6 Exterior 12 v. flood light (halogen)
- 5 Interior 12 v. strip light
- 2 12 volt rotating beacon light

- Painting Equipment & Accessories -

- 3 Paint body complete - one solid urethane color / List color:
 Note: Due to variations in OEM paint products and application methods,
 Maintainer cannot guarantee a perfect paint match on colors or metallic.
 Note: For metallic or clear coat/base coat paint additional charges
 will be required and are not included in this quote unless shown
- 1 Line-X protective spray covering - deck platform & steps, above body
 compartments and reel compartment top, front & interior

- Roll-out Drawer and Tray Equipment & Accessories -

- 1 EZ Latch Aluma custom drawer HD set (250 lb. cap. Ea.) 32"W x 18"D x (3)-4"H
 w/ 1 F-B divider & 4 S-S adj. Dividers
- 1 Used filter storage cabinet mounted on roll-out tray
- 1 Used filter storage cabinet plumbed into evac system

- Miscellaneous Equipment & Accessories -

- 1 Vise / grinder removable mounting plate

- Lube Tanks -

Tanks equipped with filtered fill caps, suction screen, guarded sight
 gauge, shut-off valve on tank suction line, tank baffles and tank rack

- Steel Lube Tanks -

- 1 65 gallon steel tank - 90 WT
- 3 200 gallon steel tanks - Hydraulic, 15/40, T04
- 1 300 gallon steel tank - Evac
- 2 600 gallon steel tanks - Diesel

- Stainless Steel Lube Tanks -

- 1 100 gallon stainless steel tank - water/ anti-freeze Green
- 1 125 gallon stainless steel tank - water/ anti-freeze Red

- Plastic Lube Tanks and Other Tank Accessories -

- 4 110 volt coil heater (in tank) for oil products / max. 2 heaters per plug
- 1 Product heaters to be wired to generator, run in conduit
- 1 Sealed duplex electrical outlet w/ (2) male plug-ins, wire to heaters, run in conduit
- 1 Sealed electrical outlet w/ (1) male plug-in, wire to grease heater, run in conduit
- 1 Safety curcuitry for proper power supply
- 1 "Tank Full" indicator light - evac

- Hydraulic Driven Pump Kits -

- 4 Hydra Kit #1 Oil - Commercial-Shearing pump (small displacement)
 0-8 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.
 0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.
 Hannay 1/2" X 50' spring reel & high-flow non-drip rigid dispenser
- 2 Hydra Kit #4 Anti-Freeze - Hypro pump (non-corrosion resistant)
 0-10 GPM delivery
 Hannay 1/2" X 50' spring rewind (non-corrosion resistant)
 high-flow non-drip rigid dispenser
- 1 Hydra Kit #5 Evacuation - Commercial-Shearing pump
 0-10 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.
 0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.
 Hannay 1" X 30' spring reel, 4-way control & suction screen
- 1 Hydra Kit #8 Fuel - Commercial-Shearing pump

20-25 GPM delivery
Hannay 1" X 45' spring rewind reel
1" OPW dispenser & swivel

- Air Driven Pump Kits -

- 1 Air Kit #12 120# Grease Kit - Graco 50:1 pump (regulator & oiler)
drum cover, follow plate & tie down
Hannay 3/8" X 50' spring rewind reel w/ high pressure swivel
dispenser with swivel

- Lube Equipment & Accessories -

- 2 Air operated emergency fuel shut-off w/ fusible link
- 1 Fuel meter 0-30 GPM
- 4 Digital oil meter 12 GPM w/ non-drip dispenser in lieu of std.
- 1 120# grease drum heater (120 volt / 700 watt)