



## Z217 Equipment

### - Standard Features -

- Galvannealed body to resist corrosion including body shell (12 ga), bulkhead, wheel skirting and all exterior sheeting / Aluminum doors (3/16" thick)
- Doors are single piece construction to avoid water traps
- Three point D-Ring door latches / Gas Shock door holders
- Under body is undercoated to resist corrosion w/ reinforcements and drain plugs
- I.C.C. round recessed lights, reflectors, mud flaps and rear body grab handles

### 13.5 Feet of heavy duty lube bed w/ I.C.C. bumper: Multi-leaf or air suspension recommended / other suspension types consult factory for approval

- 1 Galvannealed rear reel compartment w/ aluminum roll-up access door, rear vapor proof switch panel & open grated deck span in rear step
- 4 Galvannealed underbody storage compartment
- 4 Galvannealed above body storage compartment
- 1 Permanent steps built flush on outside of bed
- 1 Permanent steps built recessed into side of bed
- 1 Install charge to mount lube body on chassis

### - Chassis Equipment & Accessories -

- 1 Electric back up alarm - 97 db at 1 meter
- 1 PTO for Allison auto transmission in lieu of std manual
- 1 Electronic engine spd. control - computer set - electronic engine
- 1 Mini ICC safety kit - 2 1/2 lb fire ext. ABC, hazard reflectors
- 1 Fire extinguisher - 20 lbs (ABC)
- 1 Four hazard placard flip triangles - required w/110 gal. or greater

### - Hydraulic Equipment & Accessories -

- 1 PTO driveline - high displacement hydraulic pump
- 1 Lrg. closed center LS hydraulic power pkg, includes PTO, lrg. pump, large oil reservoir w/ in-tank filter, vent fill cap, sight gauge

### - Compressor Equipment & Accessories -

- 1 Model 65 Viking rotary screw hydraulic driven air compressor w/ cover 65 CFM @ 150 PSI, w/ 20 gallon air tank & build in system oil cooler requires: large pump kit not included
- 1 Air accessory package - filter / lubricator / regulator 1/2" X 50' spring rewind reel, hose & ball stop

### - Compartment Equipment & Accessories -

- 7 Adjustable shelf

### - Lighting / Electrical Equipment & Accessories -

- 6 Exterior 12 v. flood light (halogen) - (2) rear & (2) each side
- 6 Interior 12 v. strip light

### - Painting Equipment & Accessories -

- 2 Paint body complete - one solid urethane color / List color:  
Note: Due to variations in OEM paint products and application methods, Maintainer cannot guarantee a perfect paint match on colors or metallic.

Note: For metallic or clear coat/base coat paint additional charges will be required and are not included in this quote unless shown

- 1 Line-X protective spray covering - deck platform & steps, above body compartments and reel compartment top, front & interior

- Roll-out Drawer and Tray Equipment & Accessories -

- 1 EZ Latch Aluma (7) drawer HD set (250 lb. cap. Ea.) 29"W x 18"D x (1)-6", (1)-5", (5)-4"H, overall height 40.5" / 2 F-B dividers & 6 SS adj. Dividers
- 1 Used filter storage cabinet mounted on roll-out tray
- 1 Used filter storage cabinet plumbed into evac system

- Lube Tanks -

Tanks equipped with filtered fill caps, suction screen, guarded sight gauge, shut-off valve on tank suction line, tank baffles and tank rack

- Steel Lube Tanks -

- 1 60 gallon steel tank - 50 WT
- 1 75 gallon steel tank - Transmission
- 1 100 gallon steel tank - 90 WT
- 2 150 gallon steel tanks - 30 WT & 15/40
- 1 200 gallon steel tank - Evac

- Stainless Steel Lube Tanks -

- 1 130 gallon stainless steel tank - anti-freeze

- Plastic Lube Tanks and Other Tank Accessories -

- 5 110 volt coil heater (in tank) for oil products / max. 2 heaters per plug
- 1 Tank full indicator light w/audible alarm - evac

- Hydraulic Driven Pump Kits -

- 5 Hydra Kit #1 Oil - Commercial-Shearing pump (small displacement)  
0-8 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.  
0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.  
Hannay 1/2" X 50' spring reel & high-flow non-drip rigid dispenser
- 1 Hydra Kit #4 Anti-Freeze - Hypro pump (non-corrosion resistant)  
0-10 GPM delivery  
Hannay 1/2" X 50' spring rewind (non-corrosion resistant)  
high-flow non-drip rigid dispenser
- 1 Hydra Kit #5 Evacuation - Commercial-Shearing pump  
0-10 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.  
0-4 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F.  
Hannay 1" X 30' spring reel, 4-way control & suction screen
- 1 Hydra Kit #13 400# Grease Kit - Graco 5:1 pump  
drum cover, follow plate & tie down  
Hannay 3/8" X 50' spring rewind reel w/ high pressure swivel dispenser with swivel

- Lube Equipment & Accessories -

- 1 400# grease drum heater (120 volt / 1200 watt)