



AATAC AMD SERIES CARRIER

Standard Equipment

- 17' - 22' steel or 19' aluminum body
- Dual front lift cylinders
- Extension cylinder with wear rings
- Tubular cab protector
- 96" wide body
- Dual illuminated control panels
- 6" solid sides
- Positive lockdown system
- Chassis reinforcing subframe
- 3/4 length subframe
- Full length nylatron slide pad
- Safety straps and ratchets
- Tow light socket
- Variable speed hydraulic winch
- Four rear tie down slots
- 36"x14"x16" tool box with key
- 50' Wire rope
- Mud flaps
- One 5' safety chain
- Two 8' chains with J-hooks
- PTO pump combination
- Complete installation hardware
- Sealed wiring connectors
- Factory pre-installed and tested

Options

- Wire rope tensioner
- Winch remote free spool
- Extra tool boxes
- Stainless tool box door covers
- Stake pocket sides (steel only)
- Removable side rails (steel only)
- Various cab protectors
- Snatch block
- Light bar
- Deluxe switch panel
- Work lights
- Hook up lights
- Side D-rings
- Tool box lights
- Pintle hitch
- Trailer hitch
- V-chains and straps

Specifications		
	Steel	Aluminum
Load capacity	14,000	10,000
Platform size	19' - 22'	18'8" - 8"
Floor	3/16" Solid smooth plate	3/16" extruded aluminum
Crossmembers	3"x4.1 58,000 PSI	3"x4.1 58,000 PSI
Wire rope	50' 3/8" 6x37	50' 3/8" 6x37
TowBar capacity	3,500 extended	3,500 extended
Wheellift capacity	2,500 extended	2,500 extended
Winch	10,000 lb hydraulic	10,000 lb hydraulic

Chassis recommended 14,250 to 24,000 GVW