

KARGO KING II

The Kargo King II was developed over a decade ago specifically for the needs of the rental industry providing a fast, efficient and safe system to deliver a majority of their equipment. The low deck height allows for the transport of taller loads along with providing better stability with its low center of gravity. With the bed deployed on the ground, the low deck and beavertail allows even difficult to load equipment such as scissor lifts to be driven, not winched on for transport. For increased operator safety, the load is secured from the ground, helping eliminate falls from a wet or oily deck. Available in deck lengths from 12 to 16 feet with load capacities of 8,000 to 12,000 lbs. the Kargo King II is ideal for city deliveries and in tight residential or business locations. The Kargo King II is more versatile and maneuverable than a stake bed or pickup truck pulling a trailer and more cost efficient than operating a partial load on a heavy tractor trailer combination. Other popular options include a loading dock leveler, a electric winch for disabled equipment and additional detachable deck and body options.



Standard Equipment

Hydraulic Chassis Frame Mounted Lifting System

- 2 Hydraulic Lift Cylinders
- Integrated Rear Body Locks
- Manual Driver Side Control Valve
- Fenders
- Mud Flaps
- Rear bumper
- Hydraulic Tank with Easy Service Filter
- Hydraulic pump
- 7 Way Tow Light Plug
- Back up Alarm
- Painted Black Urethane
- Assembled and Tested

Deck

- Steel Checker Plate Deck w/ Full Cab Protector and Kwik Attach System
- Outside Rub Rails with Stake Pockets
- Tapered Rear Approach Plate
- Wire Mesh in Front Rack
- Front Chain Racks
- Removable Rear Wheels
- Painted Black Urethane

Deck Specifications & Chassis Recommendation

| Deck Length | Capacity | G.V.W. | C.A. |
|-------------|-------------|---------------------|------|
| 12' | 8,000 lbs. | 17,800 - 19,500 lbs | 84" |
| 14' | 12,000 lbs. | 25,000 - 26,000 lbs | 108" |
| 16' | 12,000 lbs. | 25,000 - 31,000 lbs | 120" |

Optional Equipment

- Hydraulic Dock Leveler System
- Stationary Light Pylon
- 8,000 lb. Electric Slide in Winch Package
- Tall Removable Sides (30" x 43.75")
- Short Removable Side (60" x 28.75")
- 2" Receiver Hitch
- Receiver Style Pintle/Ball Attachment
- Hot Shift PTO
- Rear Work Lights
- Flashing LED Warning Light
- Tie-Down Chains
- Load Binders
- Switch Panel
- Aluminum Tool Boxes (33" or 49")
- Steel Tool Box with Stainless Steel Door (36" or 48")
- Rear Jumper Start Kit
- Additional Decks
- Installation

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and/or specifications without notice or obligation. Some equipment shown is optional.

* All Recommendations are minimums. Heavier specifications may be required depending on chassis and equipment weight.

DISTRIBUTED BY:

Miller
INDUSTRIES
©2017 Miller Industries Towing Equipment Inc.
All Rights Reserved.

8503 Hilltop Drive • Ooltewah, TN 37363
800-292-0330 • 423-238-4171
FAX 423-238-5371 • www.MillerInd.com